


FUJIFILM® AstroPore® PSE80 Flat Sheet Membrane

chemical properties	
material	Polysulfone
physical properties	
thickness	140±10µm
Breaking elongation	≥40%
Tensile strength	≥3.9MPa
Specification of membrane performance	
Bubble point (Ethanol 25°C)	0.061-0.077MPa
Water Flow Rate (water , 25°C)	174-280mL/min/cm2/bar
Packaging Specifications	
Length	342m/roll
wide	275mm±2mm
Minimal packaging	2roll/box



All specifications are based on FUJIFILM internal test procedures .

Technical Information: These information, properties, specification and other statements contained in this material are based on the evaluation and test method which is FUJIFILM believes are reliable, but it is not guaranteed the accuracy or completeness..

Product Use: The performance of FUJIFILM products in special applications may be affected depending on the user's environment. Therefore, users need to accurately assess whether they are suitable for the purpose when using FUJIFILM products.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable FUJIFILM product packaging or product literature, FUJIFILM warrants that each FUJIFILM product will conform to the applicable FUJIFILM product specifications when shipped from FUJIFILM. FUJIFILM MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the FUJIFILM product fails to comply with the terms of this warranty, the sole remedy at FUJIFILM's option is to replace the FUJIFILM product or refund the purchase price.

Limitation of Liability: Except as prohibited by law, FUJIFILM shall not be liable for any loss or damage, whether direct, indirect, special, incidental or consequential, arising out of FUJIFILM products, regardless of the legal theory asserted, including warranties, contracts , negligence or strict liability.

FUJIFILM and ASTROPORE are trademarks of FUJIFILM Company. © 2021 FUJIFILM Company. All rights reserved.

FUJIFILM (China) Investment Co.,Ltd.
Industrial Products Division
6F, Tower 7, Crystal Plaza, No.6 Lane 100, Ping Jia Qiao Road
Pudong New Area, Shanghai, P.R.China 200126
Phone:+86-021-50106000*8053

Rev. 07/2022
www.fujifilm.com

Expiration date: 3 years
Storage method: Store at room temperature indoors without external influences such as water, gas, or light.